

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: H01L 21/04

A1

(11) International Publication Number:

WO 00/16382

(43) International Publication Date:

23 March 2000 (23.03.00)

(21) International Application Number:

PCT/US99/21475

(22) International Filing Date:

16 September 1999 (16.09.99)

(30) Priority Data:

60/100,546

16 September 1998 (16.09.98) US

(71) Applicant (for all designated States except US): CREE RE-SEARCH, INC. [US/US]; 4600 Silicon Drive, Durham, NC 27703-8475 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SLATER, David, B., Jr. [US/US]; 6304 Jarratt Cove, Raleigh, NC 27613 (US).

(74) Agents: SUMMA, Philip et al.; Philip Summa, Patent Attorney, Suite 315, 13777 Ballantyne Corporate Place, Charlotte, NC 28277 (US).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of

(54) Title: LOW TEMPERATURE FORMATION OF BACKSIDE OHMIC CONTACTS FOR VERTICAL DEVICES

(57) Abstract

The invention comprises a method for forming a metal-semiconductor ohmic contact (18) for use in a semiconductor device (10) having a plurality of epitaxial layers (14a-c) wherein the ohmic contact (18) is preferably formed after deposition of the epitaxial layers (14a-c). The invention also comprises a semiconductor device comprising a plurality of epitaxial layers and an ohmic contact.

10

